

SAFETY DATA SHEET

GAS LEAK SPRAY 400mL

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME GAS LEAK SPRAY 400mL
PRODUCT NO. PH020
SUPPLIER ARCTIC PRODUCTS LIMITED
Nina Works
Gelderd Road
Leeds
LS12 6NA
0844 871 8461
0844 871 8462
Sales @ www.arctic-products.co.uk

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
CARBON DIOXIDE	204-696-9	124-38-9	1-5%	-

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Aerosol propelled by carbon dioxide.

4 FIRST-AID MEASURES

INHALATION

Not relevant.

INGESTION

Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash off with water. Get medical attention if any discomfort continues.

EYE CONTACT

Rinse the eye with water immediately. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable.

SPECIAL FIRE FIGHTING PROCEDURES

Cool containers exposed to flames with water until well after the fire is out.

UNUSUAL FIRE & EXPLOSION HAZARDS

Possible risk of can rupture when exposed to fire\high temps.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Absorb with inert, damp, non-combustible material, then flush area with water.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

CAUTION. Pressurised container. Do not expose to temperatures exceeding 50°C Do not puncture or incinerate even when empty. Avoid contact with skin and eyes. ONLY USE IN WELL VENTILATED AREAS

GAS LEAK SPRAY 400mL

STORAGE PRECAUTIONS

Store in a cool dry place away from all sources of heat including direct sunlight.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
CARBON DIOXIDE	OES	5000 ppm		15000 ppm		

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



HAND PROTECTION

Chemical resistant gloves required for prolonged or repeated contact.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Aerosol

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

11 TOXICOLOGICAL INFORMATION

INGESTION

May cause irritation of mouth, respiratory tract and intestinal system.

SKIN CONTACT

May cause skin irritation/eczema

EYE CONTACT

May cause mild irritation or discomfort.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not classified as dangerous to the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Do not puncture or incinerate even when empty. Dispose via Waste Disposal Contractor in accordance with local authority guidelines.

14 TRANSPORT INFORMATION

PROPER SHIPPING NAME	AEROSOL		
UN NO. ROAD	1950	ADR CLASS NO.	2.2
ADR CLASS	Class 2.2: Non-flammable, non-toxic gases.	ADR LABEL NO.	2.2
UN NO. SEA	1950	UN NO. AIR	1950

GAS LEAK SPRAY 400mL

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

S2 Keep out of the reach of children

S9 Keep container in a well-ventilated place.

S23 Do not breathe vapour/spray.

S35 This material and its container must be disposed of in a safe way.

16 OTHER INFORMATION

REVISION DATE 19/2/10

DATE 23/9/08

RISK PHRASES IN FULL

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.